

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



7

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C12P 7/18, C12N 11/00		A1	(11) International Publication Number: WO 00/04181 (43) International Publication Date: 27 January 2000 (27.01.00)
(21) International Application Number: PCT/FI99/00573 (22) International Filing Date: 29 June 1999 (29.06.99) (30) Priority Data: 981615 15 July 1998 (15.07.98) FI (71) Applicant (for all designated States except US): XYROFIN OY [FI/FI]; P.O. Box 213, FIN-48101 Kotka (FI). (72) Inventors; and (75) Inventors/Applicants (for US only): OJAMO, Heikki [FI/FI]; Veijolantie 15, FIN-08150 Lohja (FI). KOIVIKKO, Hannu [FI/FI]; Rajakallio F, FIN-02460 Kantvik (FI). HEIKKILÄ, Heikki [FI/FI]; Ristiniementie 32 D 33, FIN-02320 Espoo (FI). (74) Agent: BORENIUS & CO. OY AB; Kansakoulukuja 3, FIN-00100 Helsinki (FI).			(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: PROCESS FOR THE PRODUCTION OF MANNITOL BY IMMOBILIZED MICRO-ORGANISMS			
(57) Abstract The invention relates to the production of mannitol by bioconversion with the aid of immobilized micro-organisms as well as to the use of the mannitol and by-products formed in the conversion process. In said process a solution containing a substrate convertible into mannitol is fed into contact with solid carrier particles containing viable mannitol-forming micro-organism cells immobilized in and/or on said particles. The solution is reconditioned between successive conversion steps in order to provide conversion of a major portion of said substrate into mannitol.			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KI	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Process for the production of mannitol by immobilized micro-organisms

The present invention relates to the production of mannitol by bioconversion with the aid of immobilized micro-organisms, especially to the bioconversion of a mannitol producing substrate by viable immobilized mannitol-forming micro-organisms. The invention also relates to the use of the mannitol and by-products formed in the conversion process.

Mannitol is a six-carbon sugar alcohol having wide use in several industrial areas. Examples of food use are as a sweetener, an anti-caking and a free-flowing agent. Pharmaceutical applications are as an excipient and a diluent for solids and liquids, as an osmotic diuretic and as a protective agent in surgery. Mannitol is also used for making resins and plasticizers.

Low levels of mannitol are found in several fruits and vegetables. Some algae and mushrooms contain significant concentrations of mannitol. Mannitol has been recovered from manna and seaweeds. Presently mannitol is industrially produced by catalytic hydrogenation of fructose or glucose/fructose mixtures such as invert sugar. Raney-nickel is used as the catalyst. The disadvantage of this method is that only about half of the fructose is converted to mannitol. The other half goes to sorbitol as does all of the glucose. Mannitol is far less soluble in water than sorbitol and thus crystallization is used for the separation of these two compounds. As Raney-nickel is used as the catalyst, the raw material being hydrogenated must be quite pure to avoid poisoning of the catalyst.

Mannitol may be produced also from mannose and glucose by hydrogenation. Several micro-organisms are known to produce mannitol. Among bacteria a heterofermentative bacterium *Leuconostoc mesenteroides* seems to be the most efficient of these. Soetaert W., Med. Fac. Landbouw. Rijksuniv. Gent, (1990) 55/4:1549-52, has described this fermentative method with free cells providing a 80-90 % yield of mannitol from fructose. Later Soetaert W. *et al.*, Agro-Food Industry Hi-Tech, Jan/Feb 1995:41-45, showed up to 94 % yield with free cells in a fed-batch process with a mutant strain. This fed-batch fermentation resulted in an average volumetric productivity of 3.5 g/lh in a broth containing significant concentrations of nutrients to enable cell growth. Cell growth is a prerequisite for the production in such a system.

Soetaert *et al.*, Bioorganic Chemistry in Healthcare and Technology, Eds. Pandit U.K. and Alderweireldt F.C., Plenum Press, New York, 1991, also tried to apply a continuous bioreactor with the cells immobilized on polyurethane, but the result was poor, achieving

only about 50 % yield of mannitol from fructose. In the above mentioned 1995 article Soetaert *et al.* explained this to be caused by the low affinity of the fructose to mannitol converting enzyme - mannitol dehydrogenase. According to Soetaert the low yield is a consequence of the use of an immobilized bioreactor.

EP 0 683 152, Araya *et al.* (1991), discloses a similar free cell method, but with a *Lactobacillus* sp. B001 strain. This gives 60 % yield of mannitol from fructose. They also claim separation of acetic acid and lactic acid from the broth.

In JP 62239995, Hideyuki *et al.* (1987), teaches a process wherein free cells of *eg. Lactobacillus brevis* IFO 3960 and *L. mesenteroides* IFO 3426 are used for mannitol production.

Yun *et al.* Biotechnol. Lett. (1996), 18:1145-1150, give some data about a fermentative mannitol production with free cells of another lactic acid bacterium *Lactobacillus* sp. KY-107. No glucose addition is needed and the mannitol yield from fructose is 71 %. Formation of other extracellular products are not shown. The average volumetric productivity can be calculated from the results to be about 0.9 g/lh.

Onishi *et al.*, Biotechnol. Bioeng., (1970), 12:913-920, discloses a process providing a 50 % yield of mannitol from glycerol with free cells of a *Torulopsis versatilis* strain.

Several filamentous fungi (molds) produce mannitol from glucose as well. According to Hendriksen *et al.*, J. Chem. Tech. Biotechnol., (1988), 43: 223-228 the best of these is *Aspergillus candidus* giving a 50 % yield of mannitol from glucose. Production with yeast and filamentous fungi gives lower volumetric productivities than with bacteria. All the reports work with free cells.

The prior art biotechnical processes for the conversion of sugars to mannitol have not proven entirely satisfactory and therefore the industrial production is still primarily based on hydrogenation. Bioconversions using free mannitol-forming microorganisms are not entirely suitable for large scale production and systems with immobilized systems have so far not provided an adequate conversion yield. The volumetric productivity of the prior art systems is low leading to uneconomical operations.

Thus, there remains a need for improving the bioconversion of fructose and other substrates into mannitol in order to provide an industrially acceptable process.

An object of the present invention is thus to overcome disadvantages of the prior art techniques for converting substrates into mannitol and to provide a technically feasible biotechnical process for the production of mannitol.

An object of the present invention is also to provide a process for converting suitable substrates into mannitol by viable micro-organisms immobilized on a solid carrier.

A further object of the invention is to provide a continuous process for converting substrates into mannitol in a packed column, in which the solution is reconditioned during the conversion for increasing the yield.

Another object of the invention is to provide a process wherein a solution containing a substrate convertible into mannitol is sequentially reconditioned to provide optimum conditions for the conversion by immobilized microorganisms.

An object of the invention is also to provide a process for producing mannitol in a packed column with a low resistance to flow and a low pressure drop at flow of a substrate solution through said column.

An object of the invention is also to provide a process which utilizes a packed column having an acceptable flow rate through the column.

An object of the invention is also to produce mannitol from fructose-containing solutions which inherently contain a co-substrate such as glucose for the conversion.

An object of the invention is further to provide a biotechnical process for producing mannitol at a relatively high volumetric productivity.

Surprisingly, and contrary to prior beliefs it has been found that mannitol may be advantageously produced by micro-organisms which are immobilized in and/or on a carrier.

The present invention is defined in the appended claims, the contents of which are enclosed herein by reference.

Accordingly, the invention relates to a process for the production of mannitol by bio-

conversion with the aid of immobilized micro-organisms. Said process comprises the steps of feeding a solution containing a substrate which is convertible into mannitol into contact with solid carrier particles containing viable mannitol-forming micro-organism cells immobilized in and/or on said particles, under conditions suitable for converting said substrate into mannitol, reconditioning said solution between successive conversion steps in order to provide conversion of a major portion of said substrate into mannitol, and recovering mannitol and/or by-products of the conversion.

The preferred substrate is fructose. In the preferred bioconversion the solution also contains a co-substrate such as glucose.

The reconditioning of the solution is preferably performed in a sequential manner by adjusting one or more of the parameters of the conversion. The sequential reconditioning is preferably performed between distinct steps of the bioconversion.

In accordance with the present invention, the solution is preferably fed through a bed of immobilized microorganisms. The microorganism bed may be contained in a packed column or it may alternatively be located in an agitated reactor. In the preferred embodiment of the invention the solution is recirculated through a packed column and the solution is reconditioned as it leaves the bed, to be at its optimum for the next bioconversion sequence.

The feed solution is preferably sequentially reconditioned by adjustment of process parameters which change with time and conversion. This reconditioning according to the invention improves the conversion rate and/or the conversion yield of the process.

According to a preferred embodiment of the invention the substrate solution is sequentially reconditioned by intermittently adjusting the pH of the solution. The pH is preferably adjusted outside the actual microorganism bed by recirculating the solution through the bed and adjusting the pH between recirculations. Alternatively, the pH may be adjusted between beds in a system having several beds in series or in parallel. The beds are preferably contained in one or more columns. The solution may be fed at a relatively high flow rate through such columns.

In another embodiment of the invention, the solution is sequentially reconditioned by adjusting the concentration of mannitol producing substrate, such as fructose, or co-substrate, such as glucose, used by some microorganisms in the conversion. This recon-

ditioning of the solution allows the process to proceed sequentially at optimum conditions. It also allows a freedom in the selection of feed solution, since a solution having a low concentration of either substrate or co-substrate may be reconditioned to bring the solution up to optimum conditions.

It has also been found advantageous to sequentially adjust the temperature of the feed solution between recirculations and/or between beds or columns. The temperature of the solution should be adjusted to a value which is within the optimum temperature of the microorganism in question.

According to the present invention it has been found advantageous to proceed at a fairly high feed rate, which is enabled by the use of a packed column having the microorganisms immobilized on a substantially non-compressible carrier providing only a small resistance to flow. The feed rate may, however, also be adjusted e.g. between columns or, for instance by dividing the flow from one column into two.

A reconditioning, preferably in a sequential manner, of the nutrients in the feed solution is used according to the invention to provide, on one hand an optimum concentration of the basic nutrients necessary for the conversion, and on the other hand to intermittently refresh the immobilized microorganisms by subjecting them to conditions which provide sequential phases of increased growth with increased and supplemented nutrient feed.

In the process some conversion products are liable to cause a lowering of the conversion rate. The solution is preferably sequentially reconditioned by removal of such products by various means such as by filtration, crystallization, chromatography, ion exchange, reduction of pressure, neutralization by chemical additions, etc.

In many cases a combination of two or more of the above discussed reconditioning procedures will provide the desired optimum conditions for the conversion. It is also possible to direct part of the flow through a reconditioning step while the other part of the feed goes unconditioned. The flows may also be partitioned between different reconditioning steps in the phases between bioconversions.

According to the invention the aim is to perform said reconditioning in an amount sufficient to increase the conversion yield of mannitol compared to a non-conditioned state. Preferably, a sequential conditioning is performed so as to provide a conversion of at least 70%, preferably 80 to 90% or more of the feed fructose into mannitol.

According to a preferred embodiment of the invention the feed solution is recirculated through a bed of microorganisms to increase the mannitol yield and the volumetric productivity of the system. The feed solution may also be fed sequentially through several beds of microorganisms. The process is preferably performed as a continuous conversion in one or more columns packed with a carrier containing immobilized microorganisms.

The immobilized system according to the invention enables the use of high concentration of the microbe, feeding of simple solutions of substrate with very low concentrations of nutrients and steady production for a long period with the same immobilized microbial inoculum. All this results in a high mannitol yield from the substrate (generally fructose). Yields well above 50% and as high as 80-90 % or more have been obtained. The system provides a very high volumetric productivity (above 10 g/lh and up to 30-40 g/lh) and steady production with one cell loading.

The crude conversion product contains basically just mannitol and acids such as lactic acid and acetic acid and there is no need for cell separation for the crude product. Thus, an exceptionally pure crude product is formed in the process. The substrate being converted to mannitol may be circulated back after the mannitol recovery step to sequentially increase the substrate concentration and thus to increase the conversion yield. The co-substrate may be similarly recirculated in the process. Likewise, part of the acids which are produced in the conversion may be circulated back from the recovery step to sequentially improve the asepticity of the conversion.

The mannitol yield in recovery may also be increased after most of the mannitol has been separated from the mother liquor by recirculating the mother liquor after crystallization sequentially back to the process. Mannitol remaining in the mother liquor will thus add to the mannitol produced in the conversion.

The carrier which is useful in the performance of the present process should preferably be of a non-compressible material. It may be composed of an inert material such as porous glass beads, porous silicate beads, granulated activated charcoal, or solid acidic or basic ion exchange materials. Especially good results have been obtained on a commercial scale with a weakly basic anion exchange substance in the form of a substantially non-compressible porous-surface particulate solid material. A suitable cation exchanger comprises microfibers or microparticles of basic diethylaminoethyl (DEAE) modified cellulose adherently bound by agglomeration with polystyrene to form a granulate, such as acidified

GDC carrier (e.g. Spezyme^R GDC produced by Genencor International Oy).

Ion exchangers with a strongly acidic or a basic character have not been found suitable as carrier materials.

It is preferred that the microbe immobilized on or in the carrier metabolizes sugars solely through the pentose phosphate pathway, expresses mannitol dehydrogenase activity, produces no other main reduced products than mannitol *eg.* not ethanol and is a fermentative microbe. Several heterofermentative lactic acid bacteria are examples of such microbes. Among suitable microbes can be mentioned *Leuconostoc pseudomesenteroides*, *Aspergillus candidus*, *Zygosaccharomyces rouxii*, *Candida versatilis*, *Lactobacillus fermentum*, *Lactobacillus cellobiosus*, *Lactobacillus brevis*, *Lactobacillus buchneri*, *Leuconostoc mesenteroides* and *Leuconostoc oenos*. The preferred micro-organism is *Leuconostoc pseudomesenteroides* (ATCC 12291).

The invention is not, however, limited to these microbes and other microbes with a similar activity as well as microbes derived from such microbes, for instance by recombinant techniques, may be used in the process.

Metabolism of hexose sugars through the pentose phosphate pathway generates two reducing equivalents (NAD(P)H) and one mole of pentose-5-phosphate per mole of hexose. From the one mole of pentose-5-phosphate one mole of lactic acid and one mole of acetic acid is produced in lactic acid bacteria. In this latter route there is no net consumption or production of reducing equivalents. Thus, the microbe needs a substrate to be reduced to consume the extra reducing equivalents. It is this substrate which is preferentially converted to mannitol. Most of the microbes used in the process are fermentative and thus do not need oxygen transfer.

Any assimilable hexose sugar or an oligo- or polysaccharide (*eg.* sucrose, lactose, maltose, starch, starch or cellulose hydrolysates, cellobiose, cellulose) hydrolyzable into such hexose sugars or complex sources containing these can be used as a co-substrate. The preferred substrate is fructose which is convertible to mannitol. In some cases mannose functions according to the invention as a substrate in an equivalent way to fructose and mannose may be included in the feed solution.

Suitable feed solutions thus include mixtures of fructose and glucose, inverted molasses and/or isomerized glucose. Glucose in a feed solution may be simultaneously or separately, preferably sequentially enzymatically isomerized in the process in a separate loop or in

the same apparatus. The feed solution may comprise cane or beet molasses or fractions thereof. It may comprise thin or thick juices or even the run-offs from sugar production after first, second or third sugar crystallizations. In fact, any inverted sucrose containing material can be used as the feed material which is then reconditioned to provide a suitable solution for obtaining an optimum mannitol yield from the starting material.

The conversion process results in a crude product containing mannitol, acids such as lactic acid and acetic acid, as well as any unreacted components. If necessary or desirable, the crude product may be separated into one or several products. These products may, as described above, be recirculated to the conversion process to provide sequential reconditioning of the feed solution or they may be recovered and used for various separate purposes.

The recovery steps generally include one or more steps selected from the following non-limiting list of operations:

- concentration of the crude product;
- crystallization of mannitol;
- chromatographic separation of the different products from the crude product;
- concentration of those products;
- crystallization of separated mannitol;
- separation of products from the mannitol crystallization mother liquor; and
- distillation of acetic acid and/or lactic acid.

The mother liquor after mannitol separation contains lactic acid and/or acetic acid and according to the invention this mother liquor may be used as an animal feed or a food or feed additive, e.g. as a preservative.

The above mentioned Soetaert *et. al* 1995 article teaches that the affinity of some of the mannitol dehydrogenases for fructose is rather low. This results in decreasing volumetric productivity near and below the K_m -value (about 7 g/l of fructose for *L.pseudomesenteroides*). To avoid this without losing any fructose, the present invention preferably includes a chromatographic separation step for the crude product or for the mannitol crystallization mother liquor and recycling of the separated fructose back for sequential reconditioning in the conversion step. This method can be applied with any pair of enzyme and substrate having a low mutual affinity.

The optimum conversion conditions depend on the microbe being used. Especially the pH

of the broth and the process temperature are important parameters and should be preferably sequentially adjusted into values suitable for the microbe. As acids are produced, the pH may be controlled by controlling the co-substrate consumption in such a way that the pH does not decrease too much. Alternatively, the feed solution may be buffered with a compatible buffer or the pH may be adjusted by sequential addition of a base such as sodium hydroxide. The base may be added to the feed solution in the sequence when said solution is circulating outside the bed, either between recirculations in one bed or column or between two consecutive beds or columns. The pH may also be adjusted by sequential removal of the acid byproducts from the solution.

The conversion generally produces carbon dioxide as a by-product. The carbon dioxide may be allowed to freely rise to the top of the bed or column or it may be retained in the solution by applying pressure on the column. In cases where CO₂ is released the column is preferably pressurized in order to prevent CO₂ gas from upsetting the flow pattern in the column. In cases where a pressure is applied to the column, also the pH of the feed solution may be sequentially adjusted by releasing the pressure between columns or between recirculations. This will reduce the amount of dissolved carbonic acid since carbon dioxide gas will be free to escape into the atmosphere.

It is essential for the present invention that the microbe being used is immobilized in and/or on a solid carrier. Soetaert et al. (1991) used polyurethane as a carrier with disappointing results. It has now been surprisingly found that it is possible to achieve a very good result with immobilized cells when operating in accordance with the present invention.

The bed of immobilized microorganism cells may be contained in any vessel with ports for feed and outflow. Circulation of the solution outside the bed should enable temperature control and preferably agitation and it should have ports for feed, outflow and addition of compounds such as pH controlling agents, nutrients, etc. Preferably the vessel is a column. Several columns may be used in series and/or in parallel.

The invention will now be described in detail with reference to a preferred embodiment of the invention. It should, however, be understood that this description is not intended in any way as limiting the invention to this specific embodiment.

The production organism is first grown on a liquid medium enabling efficient cell mass production. In this inoculum production phase enough nutrients are added to the medium

to allow proper cell growth.

For the immobilization the inoculum is either circulated through a bed of carrier material in the production vessel or the carrier material is added to the inoculum and the cells are allowed to adhere to the material after which the material is transferred to the production vessel.

In the production step a feed solution containing the substrate and co-substrate is recirculated through the cell mass-carrier bed or fed through a series of beds.

The production vessel preferably comprises a column packed with the immobilized microorganisms on a non-compressible carrier. The system may comprise one single bed with a recirculation system or it may comprise two or more columns in series or in parallel. The columns may, for instance, be placed on top of each other with feeding ports for pH-adjusting compounds, substrate and co-substrate, nutrients, etc. being placed between the columns.

When a substantially non-compressible carrier is used in the column, the column may be fairly high, for instance 1 meter or more, while still providing a flow rate at an acceptable level. The flow direction of the solution may be either down flow or up flow.

The volumetric flow is preferably maintained at such a rate that the production of acids in the bioconversion does not reach a level where it is prohibitive to mannitol production in the bed in question. To reach optimum mannitol concentrations the feeding is performed at a rate of 2-20 bed volumes per hour, preferably about 10-20 bed volumes per hour.

The pH of the solution is sequentially adjusted to recondition the feed solution to an optimum value for the specific microorganism being used. The pH may, for instance, be adjusted by an addition of a base such as NaOH, $\text{NH}_4(\text{OH})$, KOH, etc. although other means of pH adjustment are described above. The pH should generally be reconditioned to a level between about 4 and 7, in most cases to between 4.5 and 6.5, preferably about 5.

The solution may be directed from the bioconversion stage in the bed to a intermediate vessel where pH adjustment is performed, or the pH adjustment may take place in a recirculation pipe or in a pipe leading from one column to another.

The temperature of the solution may be sequentially adjusted so as to provide close to

optimum conditions for the conversion. Adjusting the temperature of the solution to a value of about 20 to 35 °C, preferably 25 to 30°C has been found to be advantageous.

Typical substrate (fructose) concentrations are 7-200 g/l, preferably 15-160 g/l, most preferably about 50-150g/l, with corresponding co-substrate (glucose) concentrations of 4-100 g/l, preferably 8-80 g/l, most preferably about 25-75 g/l. The conversion rate is significantly lowered if the fructose concentration decreases under the K_m value of the microorganism in question. The solution should therefore be reconditioned to have a fructose level clearly above the K_m value by adding fructose sequentially between conversion phases.

It is advantageous to utilize the cell mass in a resting state during the actual bioconversion phase, wherefore very low nutrient concentrations are required in the normal feed solution. Typically yeast extract and/or tryptone in concentrations of 0.1-4 g/l is sequentially fed to the solution outside the bed. This low nutrient level is possible because the cell mass is retained by the carrier in the vessel and mannitol conversion phase needs no cell growth. The conversion rate is dependent on the total amount of active cell mass in the bed. The sequential low-level addition of nutrients will intermittently refresh the microbial activity of the cells.

As conversion proceeds, the effectivity of the bed will be gradually lowered by a lack of viable cells in the bed. Thus, a refreshing of the cell mass in the bed should be performed by preferably sequentially feeding an increased amount of nutrients to the solution for allowing the microorganisms to grow and to increase the microbial density on the carrier. The nutrients generally comprise contains yeast extract, tryptone, Na_2HPO_4 , magnesium sulphate and/or manganese sulphate.

Preferentially alternating production and refreshing cycles are performed with the same cell mass loading. When the volumetric productivity has decreased below a threshold value, a refreshing phase is started by the addition of nutrients into the feed solution. The nutrient adding sequence is maintained until a higher threshold value for the volumetric productivity is achieved. Volumetric productivity can be estimated e.g. from the consumption rate of pH controlling agent.

A reconditioning of the solution may also be performed by removing solid or liquid components from said solution. The solution may be subjected to filtration, precipitation, elution, membrane filtration, electrodialysis, fractional distillation, etc. to remove selected

components thereof.

As the carrier material is of a durable and non-compressible structure it may be re-used even after the cell mass has reached a stage where refreshing and growth no longer provides a satisfactory conversion rate. Especially the above mentioned DEAE modified cellulose/polystyrene carrier, GDC, is capable of being regenerated. This is performed by removal of the micro-organism cells, washing and reloading the carrier with fresh viable micro-organism cells.

After a desired bioconversion phase, the solution is taken to the recovery phase. This may be started before all substrate being converted to mannitol is consumed. This is advantageous in cases where the productivity and/or yield diminishes with low substrate concentration. For example, this is the case when *L.pseudomesenteroides* is used for converting fructose. To avoid losing this unconsumed substrate, the fructose is separated in the recovery phase and circulated back to the conversion step for reconditioning the feed solution.

Contamination with foreign organisms is a frequent problem in fermentation. A mixture of lactic acid and acetic acid is inhibitory to most microbes. This can be utilized in the present invention by separating the acids in the recovery step and circulating part of them back to the conversion step to provide a sequential reconditioning of the feed solution.

In the recovery step mannitol can be directly crystallized with known techniques from the crude product after the conversion step. If complex materials are being used, color removal may be necessary before crystallization. Mannitol may also be crystallized from the solution between the bioconversion sequences to recondition the feed solution for the subsequent conversion stage.

Other sugars, if present, may be separated from the other components e.g. by chromatography and circulated back to the conversion step.

The acids produced in the conversion may be separated from the crystallization mother liquor by chromatography e.g. using a cation exchange resin in Na-form or by using ion-exchange techniques. Alternatively, the mother liquor may be used as such as an anti-microbial agent or used as described above for sequential reconditioning.

In the following the invention will be illustrated by some non-limiting examples.

Example 1

Immobilisation of the microorganism in a column reactor

L. pseudomesenteroides (ATCC 12291) was inoculated from a storage cultivation onto a growth medium having the following composition: 100 g/l fructose, 50 g/l glucose, 2 g/l yeast extract, 2 g/l tryptone, 2 g/l K_2HPO_4 , 0.01 g/l $MgSO_4$, 0.01 g/l $MnSO_4$.

The inoculum was allowed to grow over night and the cell mass was then transferred to a disinfected (70 % ethanol) carrier by recirculating the growth medium through a column packed with carrier for 2 hours. The carrier was a weakly basic anion exchange (Spezyme^R GDC carrier made of microfibers of DEAE modified cellulose bound together with polystyrene, produced by Genencor International Oy).

Example 2

Immobilisation of the microorganism in an agitated reactor

The same microorganism cell mass was used as in Example 1. The microbial cell mass was added to a reactor containing a disinfected carrier and the mixture was agitated for two hours until the microorganisms had adhered onto the carrier. Thereafter the reactor was ready for bioconversion.

Example 3

Sequential reconditioning by adjusting pH and temperature

The column provided in accordance with Example 1 (bed volume 1 liter) as used in the test. A sterilized feed solution (volume 10 liters) was recirculated through the column. The feed solution had the following composition: 150 g/l fructose, 50 g/l glucose, 1 g/l yeast extract, 1 g/l tryptone, 0.01 g/l $MgSO_4$, 0.01 g/l $MnSO_4$. The recirculation direction was from top to bottom of the column.

The temperature and pH of the feed solution was sequentially adjusted between bioconversion phases in a recirculation vessel. The temperature was adjusted to about 25°C and the pH was adjusted to 5.0 by sequentially adding NaOH (16 %).

The feed rate through the column was maintained at a constant value to provide a retention in the column of about 6 min.

After a total process time of 43 hours the composition of the feed solution was analyzed and it was found to contain: 127 g/l mannitol, 32 g/l D-lactate, 22 g/l acetate, 2 g/l fructose and 0.3 g/l glucose. The average volumetric mannitol production rate per column volume was calculated to be 30 g/lh. The mannitol yield from fructose was about 85 %.

The solution was evaporated to a 60 % dry substance content and the mannitol was crystallized from the solution by gradually cooling the solution to 32°C.

Example 4

Sequential reconditioning by adjusting nutrient feed

The recirculated batch process of Example 3 was repeated after the first converted solution had been discharged from the recirculation vessel to mannitol recovery. The recirculation vessel was refilled with a new feed solution having the same composition as the one used in Example 3.

The converted solution after the second conversion had a composition which did not significantly differ from the one obtained in the first run.

New batches of feed solution were converted in the same manner until the conversion rate, measured by the rate at which pH adjusting NaOH was consumed, decreased below a threshold value.

When the threshold value was set at 10 g/lh, the batches could be repeated for 3 to 4 runs. Thereafter the microorganisms in the column were refreshed by circulating a nutrient-rich solution containing 100 g/l fructose, 50 g/l glucose, 2 g/l yeast extract, 2 g/l tryptone, 2 g/l K_2HPO_4 , 0.01 g/l $MgSO_4$ and 0.01 g/l $MnSO_4$ through the column, until the pH adjusting NaOH consumption rate increased to a desired level (for about 3-5 hours). Thereafter the column was again used for conversion according to Example 3.

Example 5

Production of mannitol from different raw materials

By utilizing the over-all procedure described in Example 3 mannitol was produced in a recirculated packed column reactor from various raw materials and using various carrier materials. The microorganism used was *L.pseudomesenteroides* (ATCC 12291). All of the

carriers and raw materials produced mannitol under the process conditions.

The raw materials and carriers of the tests are presented below:

Table 1

Raw material	Carrier
Pure fructose-glucose mixture (3:1)	GDC (DEAE)
as above	GDC (COO ⁻)
as above	glass beads
as above	Norton catalyst
Beet molasses fully inverted with invertase (sugar 50g/l)	GDC (DEAE)
as above	glass beads
Glucose (50 g/l) isomerized to glucose/fructose (40:60)	GDC (COO ⁻)
as above	Norton catalyst

The carrier materials used were:

GDC (DEAE) = Spezyme^R GDC a weakly basic anion exchanger produced by Genencor International Oy

GDC (COO⁻) = a weakly acid cation exchanger an experimental product by Cultor Ltd

Norton catalyst = a catalyst carrier, SA 5203 1/8" from Norton Chemical Products Corporation

Example 6

Production of mannitol with different carrier materials

L.pseudomesenteroides was immobilized on various carrier materials by cultivation in the presence of the carrier materials in MRS broth containing 40 g/l fructose. The concentration of the carrier material was 40 g/l and the cultivation in a shake flask was continued up to 20 hours at shaking rate 100 rpm at 25 °C. The carrier material with the cells attached on it was separated from the broth and loaded into a column.

Mannitol production was demonstrated by circulating a solution containing 10 g/l glucose,

30 g/l fructose, 2 g/l Na_2HPO_4 , 2 g/l $\text{NaH}_2\text{-citrate}$ and 3 g/l acetic acid through the column. The pH was controlled to pH 5.2 with NaOH. Mannitol was analyzed by HPLC from samples taken after 3 hours circulation.

The carrier materials were Spezyme^R GDC, Norton catalyst, glass beads (Schott beads, SIRAN carrier, SIKUG 023/02/B, Schott Engineering), activated carbon (granulated activated carbon, Chemvicon CPG), Amberlite IRA 93 (a weakly basic anion exchanger, Rohm & Haas), and GDC (COO^-).

Example 7

Production of mannitol with different immobilized micro-organisms

L.brevis (VTT-E-91458) was immobilized on Norton catalyst as described for the *L.pseudomesenteroides* in Example 6.

Aspergillus candidus (NRRL 305) was immobilized by cultivating it for 68 h in shake flasks at a shaking rate of 250 rpm at 28 °C in Czapek broth containing 30 g/l sucrose and 5 g/l yeast extract and 40 g/l Spezyme^R GDC. The carrier material with the organism attached on it was recovered from the broth by filtration.

In a similar way *Zygosaccharomyces rouxii* (ATCC 12572) was immobilized on Spezyme^R GDC but using YM broth, *Candida versatilis* (ATCC 20221) and (ATCC 20223) were immobilized on glass beads using ATCC broth 466.

Short-term mannitol production at acceptable levels was demonstrated with the immobilized materials with the following production media:

<i>L.brevis</i> :	30 g/l fructose, 10 g/l glucose, 2 g/l Na_2HPO_4 ; sequential adjustment of pH to 5.2
<i>A.candidus</i> :	100 g/l glucose, 1 g/l yeast extract, 0.5 g/l NaNO_3 ; sequential adjustment of pH to 7.3
<i>Z.rouxii</i> :	200 g/l glucose, 1 g/l yeast extract, 0.5 g/l urea; no pH adjustment
<i>C.versatilis</i> :	200 g/l glucose, 1 g/l yeast extract, 2 g/l K_2HPO_4 ; sequential adjustment of pH to 5.5.

Example 8

Crystallization of mannitol

A filtered mannitol solution obtained according to the process of the present invention was subjected to crystallization. The dilute mannitol solution containing about 63 % mannitol on DS was evaporated to a concentration of about 48 % by weight. The resulting solution was cooled to a temperature of about 45 °C and seeded by spontaneous crystallization. The crystallized mannitol mass was cooled in about 12 hours to a temperature of about 32 °C. The crystals were separated from the mother liquor by centrifugation and dried. In the centrifugation about 50 % washing water on DS was used and crystals were dried in an oven at 40 °C.

The mannitol yield was about 25 % on DS and about 40 % on mannitol after the centrifugation.

Example 9

Separation of mannitol from mother liquor

Mannitol was crystallized from a conversion solution according to Example 8 and the crystals were separated from the mother liquor by centrifugation. In order to purify the mannitol still left in the mother liquor, a chromatographic separation of the solution was done. The separation was performed in a chromatographic separation column as a batch process.

A separation column was filled with a strongly acidic cation exchange resin (manufactured by Finex Oy, Finland) and submerged in water. The degree of cross linking the resin was 6.0 % DVB and the average particle size about 0.35 mm. The resin had been regenerated to Na⁺-form with NaCl-solution.

Before the separation, the feed solution was filtered and the dry substance (DS) content was adjusted to 30 g/100 g. The pH of the feed solution was adjusted to pH 5.5 with sodium hydroxide. The process temperature was adjusted to 80 °C and the linear flow rate of the eluent water in the column to about 0.5 m/h.

Conductivity, pH, refractive dry substance (RDS) and the composition of residual and product fractions (by HPLC) were analyzed. The compositions of the fractions and feed solution are presented in Table 2. The fractions were analyzed by HPLC.

Table 2. Composition of fractions, feed solution and mannitol yield

	Feed solution	Residual fraction	Product fraction
RDS, g/100g	30	6.5	7
Mannitol, % on DS	48.5	5	90
Glucose, % on DS	0.4	-	0.8
Fructose, % on DS	1.8	-	3.5
Acetic acid, % on DS	19	56.5	2.8
Lactic acid, % on DS	29	37	2
Mannitol yield, %		5	95

Claims

1. A process for the production of mannitol by bioconversion with the aid of immobilized micro-organisms, characterized by
 - feeding a solution containing a substrate convertible into mannitol into contact with solid carrier particles containing viable mannitol-forming micro-organism cells immobilized in and/or on said particles, under conditions suitable for converting said substrate into mannitol,
 - reconditioning said solution between successive conversion steps in order to provide conversion of a major portion of said substrate into mannitol, and
 - recovering mannitol and/or by-products of the conversion.
2. A process according to claim 1, characterized in that said reconditioning of said solution comprises sequential adjustment of pH, temperature, feed rate, substrate content, co-substrate content, nutrient feed or pressure, removal of conversion products or other solid or liquid components, or a combination of any of the foregoing.
3. A process according to claims 1 or 2, characterized in that said reconditioning is performed on a part of said solution or that different parts of said solution are subjected to different reconditioning steps.
4. A process according to claims 1-3, characterized in that said substrate comprises fructose.
5. A process according to claim 4, characterized in that the conversion is performed until at least 70%, preferably 80 to 90% or more of the fructose in said solution has been converted into mannitol.
6. A process according to any one of the preceding claims, characterized in that said carrier particles are of a porous and substantially non-compressible material.
7. A process according to claim 1, characterized in that said process is a continuous conversion process performed successively in one or more columns packed with said carrier.
8. A process according to claim 6 or 7, characterized in that said solution is recirculated through one or more of said columns.

9. A process according to claim 6 or 7, characterized in that said solution is fed successively through a series of said columns.
10. A process according to any one of the preceding claims, characterized in that said carrier is composed of an inert material such as porous glass beads, porous silicate beads or active charcoal.
11. A process according to any one of the preceding claims, characterized in that said carrier is composed of a weakly basic anion exchange substance in the form of a substantially non-compressible porous particulate solid material, preferably a weakly basic anion exchanger containing diethylaminoethyl (DEAE) modified cellulose adherently bound by agglomeration with polystyrene.
12. A process according to any one of the preceding claims, characterized in that said micro-organisms are selected from the group consisting of *Leuconostoc pseudomesenteroides*, *Aspergillus candidus*, *Zygosaccharomyces rouxii*, *Candida versatilis*, *Lactobacillus fermentum*, *Lactobacillus cellobiosus*, *Lactobacillus brevis*, *Lactobacillus buchneri*, *Leuconostoc mesenteroides* and *Leuconostoc oenos*.
13. A process according to claim 11, characterized in that said micro-organism is *Leuconostoc pseudomesenteroides* (ATCC 12291).
14. A process according to any one of the preceding claims, characterized in that said reconditioning comprises adjusting the pH of said solution to a value above about 4, preferably between pH 4.5 and 6.5, most preferably to about pH 5.
15. The process according to claim 14, characterized in that the pH of said solution is adjusted by adding a base such as an alkali hydroxide or ammonium hydroxide or by adding a buffering substance.
16. The process according to claim 14, characterized in that the pH of said solution is adjusted by removing acid formed during the conversion.
17. The process according to claim 16, characterized in that carbonic acid formed by dissolution of carbon dioxide produced during the conversion is removed by reducing the pressure of said solution.
18. A process according to any one of the preceding claims, characterized in that

said reconditioning comprises adjusting the temperature of said solution to a value of about 20 to 35 °C, preferably 25 to 30°C.

19. A process according to any one of the preceding claims, characterized in that said reconditioning comprises adjusting the volumetric flow rate of said solution to a value of about 2 to 20 bed volumes per hour, preferably about 10 to 20 bed volumes per hour.

20. The process according to claim 4, characterized in that said reconditioning comprises adjusting the substrate fructose content of said solution to about 7 to 200 g/l, preferably about 15 to 160 g/l, most preferably about 50 to 150g/l.

21. The process according to claim 20, characterized in that said reconditioning comprises adjusting the co-substrate content of said solution to about 4 to 100 g/l, preferably about 8 to 80 g/l, most preferably about 25 to 75 g/l.

22. The process according to any one of the preceding claims, characterized in that said reconditioning comprises adding nutrients to said solution for intermittently refreshing the microbial activity of the immobilized micro-organism cells.

23. The process according to claims 20 or 21, characterized in that said nutrients are selected from yeast extract, tryptone, Na_2HPO_4 , magnesium sulphate, manganese sulphate and mixtures thereof.

24. The process according to any one of the preceding claims, characterized in that said reconditioning comprises recovering mannitol between successive conversion steps.

25. The process according to claim 24, characterized in that said reconditioning comprises returning any substrate remaining in the mother liquor after final mannitol recovery to said solution.

26. The process according to claim 24, characterized in that said reconditioning comprises recovery of acids from said solution by chromatography and/or ion exchange.

27. A process according to claim 23 or 25, characterized in that said reconditioning comprises returning at least a part of said mother liquor or said recovered acid to said solution.

28. The process according to any one of the preceding claims, characterized in that said reconditioning comprises removing solid or liquid components contained in said solution by one or more processes selected from filtration, precipitation, elution, membrane filtration, electrodialysis, and fractional distillation.
29. The process according to claim any one of the preceding claims, characterized in that said reconditioning is monitored so as to provide a volumetric productivity of mannitol above 10 g/lh, preferably between 30 and 40 g/lh in said conversion.
30. The process according to claim 8, characterized in that said solution is recirculated through said column until the volumetric productivity of mannitol in said column has decreased to a predetermined threshold value.
31. The process according to claim 4, characterized in that said solution contains as a co-substrate an assimilable hexose sugar, such as glucose, or an oligo- or polysaccharide hydrolyzable to a hexose sugar, or a mixture thereof.
32. The process according to claim 31, characterized in that said feed solution contains a mixture of fructose and glucose.
33. The process according to claim 32, characterized in that said feed solution comprises isomerized glucose, inverted molasses, beet or cane molasses, thin or thick juices or fractions thereof.
34. The process according to claim 32, characterized in that glucose in said solution is simultaneously or separately, preferably sequentially enzymatically isomerized in the process.
35. The process according to claim 1, characterized in that said solution contains glucose or mannose as said substrate convertible into mannitol.
36. The process according to any one of the preceding claims, characterized in that the carrier is regenerated by removal of the micro-organism cells, washing and reloading with fresh viable micro-organism cells.
37. The process according to claim any one of the preceding claims, characterized in that mannitol is recovered from the final converted solution by crystallization.

38. The process according to claim 37, characterized in that lactic acid and/or acetic acid contained in the mother liquor after mannitol separation are recovered by chromatography and/or ion exchange.

39. Use of the mother liquor obtained according to the process of any one of claims 1 to 38 as food additive, animal feed or animal feed additive.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/00573

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: C12P 7/18, C12N 11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: C12P, C12N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Agro-Food-Industry Hi-Tech, January/February 1995, W. Soetaert et al: "Production of D-mannitol and D-lactic acid by fermentation with <i>Leuconostoc mesenteroides</i> ", page 41 - page 49 --	1-39
X	NATO ASI Series A. Life Sciences, Volume 207, 1991, W. Soetaert et al, "PRODUCTION OF MANNITOL BY LEUCONOSTOC MESENTEROIDES, IMMOBILIZED ON RETICULATED POLYURETHANE FOAM" page 249 - page 250 --	1-39
X	Med. Fac. Landbouww. Rijksuniv. Gent, Volume 55, No 4, 1990, W. Soetaert, "PRODUCTION OF MANNITOL WITH <i>Leuconostoc mesenteroides</i> " page 1549 - page 1552 --	1-39

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 November 1999

Date of mailing of the international search report

15-11-1999

Name and mailing address of the ISA:
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Hampus Rystedt/Eö
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/00573

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9704120 A1 (CULTOR OY), 6 February 1997 (06.02.97), see abstract; page 4, line 18 - page 6, line 14, claims --	1-39
A	DE 4410028 A1 (GESELLSCHAFT FÜR BIOTECHNOLOGISCHE FORSCHUNG MBH), 2 November 1995 (02.11.95), see esp. page 3, line 48 - line 51, page 4, line 63 - page 5, line 9 and fig. 1 --	1-39
A	DE 3715857 A1 (FRAUNHOFER-GESELLSCHAFT ZUR FÖRDERUNG DER ANGEWANDTEN FORSCHUNG EV), 1 December 1988 (01.12.88), see esp. column 7, lines 10-46 and fig. 1 --	1-39
A	JP 60002191 A (SHINNENRYOYU KAIHATSU GIJUTSU), 1985-01-08 (abstract) World Patents Index (online). London, U.K.: Derwent Publications, Ltd. (retrieved on 1999-11-10). Retrieved from: EPO WPI Database. DW198507, Accession no. 1985-042144: JP 60002191 (SHINNENRIYOUYU KAIHATSU GIJUTSU KENKIYUU KUMIAI) 1985-05-11 (abstract). (online) (retrieved on 1999-11-10). Retrieved from: EPO PAJ Database -----	1-39

INTERNATIONAL SEARCH REPORT

Information on patent family members

28/09/99

International application No.

PCT/FI 99/00573

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9704120 A1	06/02/97	AU 6460196 A	18/02/97
		EP 0839209 A	06/05/98
		FI 100338 B	00/00/00
		FI 953480 A	19/01/97
		US 5932455 A	03/08/99
DE 4410028 A1	02/11/95	NONE	
DE 3715857 A1	01/12/88	NONE	